

Selection Guide

Part Number	Color	Resolution	Display Size (mm×mm)	Interfaces	Driver	Dimension (mm×mm)	Pinheader
0.95inch RGB OLED (A)	65K colorful	96×64	20.14×13.42	SPI(4-wire SPI)	SSD1331	31.7×37.0	curved/horizontal
0.95inch RGB OLED (B)	65K colorful	96×64	20.14×13.42	SPI(4-wire SPI)	SSD1331	31.7×37.0	straight/vertical
0.96inch OLED (A)	1/4 yellow section, 3/4 blue section	128×64	21.7×11.2	3-wire SPI, 4-wire SPI, I2C	SSD1306	33.0×33.5	curved/horizontal
0.96inch OLED (B)	1/4 yellow section, 3/4 blue section	128×64	21.7×11.2	3-wire SPI, 4-wire SPI, I2C	SSD1306	33.0×33.5	straight/vertical
1.3inch OLED (A)	Blue	128×64	29.42×14.7	3-wire SPI, 4-wire SPI, I2C	SH1106	40.5×37.5	curved/horizontal
1.3inch OLED (B)	Blue	128×64	29.42×14.7	3-wire SPI, 4-wire SPI, I2C	SH1106	40.5×37.5	straight/vertical